

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Painted walls & trims
- > Lacquered / varnished woodwork
- > Glass, plastic, metal

ADVANTAGES AND BENEFITS

- > UV resistant
- > 14 Days Clean & easy removal
- > Clean edge

CONSTRUCTION

Overall Grade: Painter's Grade
 Backing: Crepe paper
 Adhesive: Non-solvent, specially modified UV stable adhesive

COLOR(S)

- Dark Blue
- Yellow

STANDARD SIZE

Width(s): 25mm / 1", 38mm / 1.5", 48mm / 2"
 Length(s): 25m, 55m / 60yd



Contact your Dolphin sales representative for other available sizes and colors (yellow, white).

PHYSICAL PROPERTIES

	STANDARD VALUES	UNITS
Tensile Strength	3,3	kg/cm
Adhesion to Stainless Steel 90°	< 7	N/2,5cm
Thickness	115	my
	4,6	mils
Elongation	10	%
Service Temperature Range	from -10 to +60	°C
	from 14 to 140	F

The following properties are typical and should not be considered specifications. All properties are approximate and are based on tests believed to be reliable and performed conformance with recommended test methods. These values are presented for comparison purposes and do not represent a guarantee by the manufacturer. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.