




PORTABLE SAW MACHINES







### AVAILABLE BLADES



### TECHNICAL CHARACTERISTICS



### PACKAGE



- For cutting porcelain, single-double fired, marble, granite.
- Straight, 45° bevel (Jolly) cuts, square e round knockouts, sanding/polishing.
- Unlimited size of cut.
- Maximum thickness of cut: 25 mm (1") in single pass; 50 mm (2") in double pass.
- Maximum disc: Ø 115 mm (4 1/2"); smallest blade: Ø 100 mm (4").
- Gear ratio of motor to disc 1 ÷ 2.1. Drive belt type Z90.
- The blade is cooled via heavy duty pump.
- Supplied with: turbo blade Ø 100 mm (4") for tiles, 5 abrasive discs for polishing/sanding, key kit, dressing stone, user and maintenance manual.
- Turtle shell cover helps to prevent damage when not in use.

### MODEL SPECIFICATIONS

Part No.	Barcode	Box	Lightning Bolt	M	Motor	Motor	Disc	Disc	
<b>125INOX F</b>	8024648003584	1	230 V 50 Hz	single-phase	0,9 HP / 0,66 kW	2800	100 mm	4"	5800
<b>125INOX 60</b>	8024648017055	1	230 V 60 Hz	single-phase	0,9 HP / 0,66 kW	3360	100 mm	4"	7000
<b>125INOX US</b>	8024648009265	1	110 V 60 Hz	single-phase	0,9 HP / 0,66 kW	3360	100 mm	4"	7000
<b>125INOX GB</b>	8024648009258	1	110 V 50 Hz	single-phase	0,9 HP / 0,66 kW	2800	100 mm	4"	5800

### CUTTING SPECIFICATIONS AND MACHINE DIMENSIONS/WEIGHT

Model	Disc	Blade	Blade	Blade	Blade	Blade	Machine	Weight	Box	Weight
<b>GS86</b>	100 mm	4"	18 mm	3/8"	17 mm	3/8"	45x45xh 30 cm 18"x18"xh 12"	25 Kg 55 lbs	50x50xh 35 cm 20"x20"xh 13	26 Kg 57 lbs
	115 mm	4 1/2"	25 mm	1"	17 mm	3/8"				

