



EXPLOIT 70 ADVANCED





AVAILABLE BLADES
















ACCESSORIES



PACKAGE



TECHNICAL CHARACTERISTICS



- For cutting porcelain, single-double fired, marble and granite.
- Heavy Duty water pump.
Straight, 45° bevel (Jolly) & plunge cuts.
- Sliding motor assembly with cast aluminum housing and rail supports,
- Maximum length of cut 70 cm (27 1/2").
extruded aluminum rail.
- Maximum depth of cut 45 mm (1 3/4") in single pass - straight cut, 70 mm (2 3/4") in double pass.

- Tilting motor assembly for bevel cuts (jolly) from 0° to 47°.
- Adjustable cutting depth.
- Folding legs/stand with wheels for easy transport.
- Pivoting blade guard remains parallel with tile to ensure maximum cutting depth.
- Disc flanges sizes are 25,4 mm (1") and (for Us version only) 15,9 mm (5/8").
- Maximum blade diameter 200 mm (8"); minimum 180 mm (7").
- Supplied with: continuous rim Ø 180 mm (7") diamond blade (for ceramic tile), key kit, dressing stone, user and maintenance manual.

MODEL SPECIFICATIONS

Part No.	Barcode	Box	Lightning Bolt	Motor	Motor 1	Motor 2	Disc 1	Disc 2	
392N	8024648011138	1	230 V 50 Hz	Single-phase	0,9 HP / 0,65 KW	2800	180 mm	7"	2800
392N60	8024648017079	1	230 V 60 Hz	Single-phase	0,9 HP / 0,65 KW	3360	180 mm	7"	3360
392NUSA	8024648011145	1	110 V 60 Hz	Single-phase	0,9 HP / 0,65 KW	3360	180 mm	7"	3360
392NGB	8024648017024	1	110 V 50 Hz	Single-phase	0,9 HP / 0,65 KW	2800	180 mm	7"	2800

CUTTING SPECIFICATIONS AND MACHINE DIMENSIONS/WEIGHT

Model	Disc 1	Disc 2	Blade 1	Blade 2	Blade 3	Blade 4	Blade 5	Blade 6	Blade 7	Weight	Dimensions	Weight	
EXPLOIT 70	180 mm	7"	35 mm	1 3/8"	25 mm	1"	70 cm	∞	49x49 cm	100x46xh 75 cm	42 Kg	106x56xh 67 cm	48 Kg
	200 mm	8"	45 mm	1 3/4"	35 mm	1 3/8"	27 1/2"	∞	19 1/2"x19 1/2"	39 3/8"x17 3/4"xh 29 1/2"	92 lbs	41 3/8"x21 5/8"xh 25 3/8"	106 lbs

