

ColloMatic® -

Compact mixer TMS 2000

The Allround Mixer for today's building materials

Easy to open
Tearing device

Easy transportagen
by additional rollers

Operation switch
with undervoltage
release

Fold-down step
for easy loading of the
material

Large wheels
for mobility and
maneuverability

Protective grille
for safe processing

Easy and fast cleaning
No tools needed for
detaching mixing mechanism

Segmental slide valve
at the bottom for emptying
the mixing container

Mounting for tubes; foldout



Collomix®

Collomix Rühr- und Mischgeräte GmbH



Simple feeding of mixer



Fast discharging



Easy transport to upper floor



Offset mixing tool, 3.arms



Passable for any door



Convenient transportation

**High productivity
on sides
ColloMatic® TMS**

The professional mixer with unique operation diversity

The ColloMatic® TMS compact mixer offers a professional solution for the preparation of ready-mixed materials supplied in sacks. Its main attributes are speed, mobility and reliability – so it saves time, energy and money.

The sack of material is opened with the aid of the tearing device and is emptied into the mixing container, passing through the protective grille. The mixing tool processes the entire contents of the container, mixing all the material evenly. High force transmission ensures optimum results, even with high-viscosity materials. When ready, the material is emptied into a mortar tub or wheelbarrow simply by opening

the segmental slide valve in the bottom of the container.

Another plus: The mixing tool and container can be cleaned with just a few hand movements.

The machine is also small, making it suitable for use even where space is at a premium. Moreover, large wheels make it highly mobile; even steps are no obstacle!

Loading the machine for transportation is effortless, thanks to additional rollers: Simply lift the mixer onto the loading surface, with the rollers underneath, and push into the vehicle.

Particular economic due to his wide range of application:

- Pointing mortar
- Plastering mortar
- Cement mortar
- Gypsum plaster
- Adhesive mortar
- Tile adhesive
- Paddledash (-16 mm)
- Screed
- Thicker knifing fillers
- Terrazzo

Technical data	TMS 2000
Article No.	37.110
max. Capacity	80 Ltr.
Motor power/tension	2 kW / 230 V
Speed mixing tool	42 rpm
Weight	104 kg
Dimensions (bxwxh)	720x690x1190 mm
Noise emission	65 db(A)

